

HM205/206/207



▣ 产品说明

205/206/207 型机械密封

205、206、207 型系轴向双端面、多弹簧、外流、传动套传动的釜用机械密封。205 系非平衡型，206 系大气端平衡型，207 系双端平衡型。本型号目前有 HG5-748-78 标准（简称 78 标）和 HG2098-91 标准（简称 91 标），其安装尺寸不同，选用时请注意。安装法兰的密封分平面（I）型与榫槽面（II）型两种。请在标定型号后加注。也可按用户尺寸要求加工。

标	20	21	21	21	24	24	24	24	28	28	28	28	33	33	33	33	33	33	40	40	40	40	46	46	46	46	46	52	52	52
	6	5	5	5	5	5	5	5	0	0	0	0	5	5	5	5	5	5	5	5	5	5	0	0	0	0	0	0	0	0
78 标	20	23	23	23	27	27	27	27	30	30	30	30	36	36	36	36	36	36	42	42	42	42	48	48	48	48	48	55	55	55
	7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5	5	5	5	5	5	5	5	5	5	5	5
D ₂ 9 1 标	16	17	17	20	20	20	20	20	22	22	22	25	25	25	28	28	28	32	32	32	35	35	35	39	39	44	44	44		
	0	0	0	0	0	0	0	0	5	5	5	5	5	5	0	0	0	0	0	0	5	5	5	5	5	5	5	5	5	
	20	20	20	20	22	22	22	22	28	28	28	28	33	33	33	33	33	39	39	39	39	44	44	44	44	44	49	49	49	
	5	0	0	0	5	5	5	5	0	0	0	0	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5
78 标	11	13	13	16	16	16	16	16	18	18	18	22	22	22	24	24	24	27	27	27	31	31	31	35	35	40	40	40		
	6	5	5	4	4	4	4	4	8	8	8	0	0	0	5	5	5	0	0	0	2	2	2	3	3	3	3	3		
D ₁ 9 1 标	20	16	16	16	18	18	18	18	24	24	24	24	29	29	29	29	29	35	35	35	35	40	40	40	40	40	46	46	46	
	5	4	4	4	8	8	8	8	5	5	5	5	8	8	8	8	8	3	3	3	3	3	3	3	3	3	2	2	2	
	20	14	14	14	17	17	17	17	20	20	20	20	25	25	25	25	25	31	31	31	31	36	36	36	36	36	42	42	42	
	6	9	9	9	5	5	5	5	3	3	3	3	9	9	9	9	9	2	2	2	2	3	3	3	3	3	1	1	1	
78 标	20	14	14	14	17	17	17	17	20	20	20	20	25	25	25	25	25	31	31	31	31	36	36	36	36	36	42	42	42	
	7	9	9	9	5	5	5	5	3	3	3	3	9	9	9	9	9	2	2	2	2	3	3	3	3	3	1	1	1	
n - 9 φ 1 标	4 - φ 14	4 - φ 18	8 -φ 18					12 -φ 18					12 -φ 23					12 -φ 26												
	20	8 -φ 18					12 -φ 18					12 -φ 23					16 -φ 23													
	20	6 -φ 14			8 -φ 23		12 -φ 23					12 -φ 25					16 -φ 26													
	20	8 -φ 23		8 -φ 25			12 -φ 25					12 -φ 30		16 -φ 30		16 -φ 33														

	7												
	205	304	310	315	320	330	358	367	370	382	400	410	420
H	206	316	322	327	332	342	370	379	382	394	412	420	430
	207	328	334	339	344	354	382	391	394	406	424	430	440