

HM250


Type: O-Ring Mechanical Seal

Temperature: -20°C to +180°C

Pressure: ≤1Mpa

Speed: ≤15m/s

Material: Q2,U2,B,V1,P,E,V,F,G



hengmi@meseal.com

d (mm)	D3	D2	D1	d1	L1	L2	L3
20	34	29	35	3	41	13	21
22	36	31	37	3	41	13	21
24	38	33	39	3	43	13	21
25	39	34	40	3	43	13	21
28	42	37	43	3	45	13	21
30	44	39	45	3	45	13	21
32	46	42	48	3	45	13	21
33	47	42	48	3	45	13	21
35	49	44	50	3	49	13	21
38	54	50	56	4	53	13	21
40	56	52	58	4	55	13	21
43	59	55	61	4	55	13	21
45	61	57	63	4	55	13	21
48	64	60	66	4	55	13	21
50	66	62	68	4	60	13	21
53	69	65	71	4	61	13	21
55	71	67	73	4	61	13	21
58	76	70	79	4	63	16	24
60	78	72	81	4	63	16	24
63	81	75	84	4	63	16	24
65	83	77	86	4	67	16	24
68	87	81	90	4	67	16	24
70	90	83	92	4	68	16	24
75	95	83	97	4	72	16	24
80	100	96	105	4	72	16	24
85	105	101	110	4	77	16	24
90	112	106	115	4	77	16	24
95	119	111	120	4	82	16	24
100	124	116	125	4	82	16	24