

HMKSB- 0 8



Type : Double Cartridge Seal
Replacement: Suit for KSB pump
Temperature: $\leq 150^{\circ}\text{C}$
Pressure: 1.0Mpa
Speed: $\leq 2000\text{r/min}$
Material : Q1,Q2,A,B,U1,U2,P,E,V,T,F,G,T2,M5

* Product description:

This series of mechanical seal is a new type of mechanical seal designed for desulfurization peripheral pump. This machine seals the structure advanced, the installation is convenient. This series mechanical seals are made of non-pressed sintered silicon carbide, 316L, fluoro rubber and other materials. The service life can be up to one year.

* Apply to the host

HMKSB (KSB) factory.

* Product features

Double end face set, rotary non-equilibrium type.
Single spring/ free rotation.
Horizontal installation, clamping type transmission.
YWN8, 2Cr13/ 304/316L, fluoro rubber/silicone rubber.
Outside circulation flushing

* Product parameters

Media: medium containing high impurity content such as gypsum and lime slurry.
Temperature: $\leq 150^{\circ}\text{C}$
Pressure: $\leq 1\text{ Mpa}$
Flushing: external circulation flushing.
Speed: $\leq 2000\text{ r/min}$.
Axle diameter: 50 mm

* Applicable industry:

Metallurgy, pharmacy, mineral, alumina, fertilizer.

* Applicable pump:

Slurry pump, dredge pump, alkali pump, mud pump.

