

## HMKSB-09



Type : Mechanical Seal  
Replacement: Suit For KSB Pumps  
Temperature :  $\leq 150^{\circ}\text{C}$   
Pressure: 1.0Mpa  
Speed:  $\leq 10\text{r/min}$   
Material : Q1, Q2, A, B, U1, U2, P, E, V, T, F, G, T2, M5

\* **Product description:** this type without blocking special centrifugal pump mechanical seal, mechanical seal manufacture by sichuan yu co. , LTD. , production, the mechanical seal structure is set outside flush mounted single end face structure, no adjustment in the process of installation and use the installation at the scene size, installation is simple, the substrate material can be chosen as 904 L, 316 L, 316, 2 cr13, friction pair of high quality hard alloy.

\* **Apply to the host**  
HMKSB ( KSB) factory.



\* **Product features**

High temperature resistance, corrosion, wear, high pressure.  
The spring receives the effective protection, the balance structure.  
Good sealing performance and long service life.

\* **Product parameters**

Limestone, gypsum slurry and other solid particle media and corrosion media.  
Temperature:  $\leq 150^{\circ}\text{C}$   
Wash:  
Speed:  $\leq 10\text{ r/min}$

\* **Application industry:** thermal power generation fine chemical industry.

\* **Working condition pump position:** slurry pump.

