

## HMKSB-19



Type : KSB Direct-Connect Pump Etabloc  
Mechanical Seal  
Replacement: Suit KSB Pumps  
Temperature:  $\leq 140^{\circ}\text{C}$   
Pressure :  $\leq 16\text{Mpa}$   
Speed:  $\leq 1450\text{r/mim}$   
Material : Q1,Q2,U2,T,V,M1,F,G,M

### \* Product description

Etabloc mechanical seal is applied to spray irrigation, irrigation, drainage, central heating, water supply system, air conditioning system, swimming pool, hot water, fire fighting system, cooling water, fire fighting water, seawater, oil, brine, drinking water, detergent, alkali water, industrial water, etc. Single-stage direct-connected single-stage radial split vortex shell, rated power in accordance with EN 733 standard, with replaceable shaft sleeve tube and pump body seal ring. Design in accordance with ATEX.

### \* Apply to the host

HMKSB Company

### \* Product features

It is used for sprinkling irrigation, irrigation, drainage, central heating, water supply system, air conditioning system, swimming pool, hot water, fire fighting system, cooling water, fire fighting water, seawater, oil, brine, drinking water, detergent, alkali water, industrial water, e

### \* Applicable industries :

HMKSB direct- connected pump



[www.hengmiseal.com](http://www.hengmiseal.com)