

HMMA-09(SCB428-2.5",3",3.5")



Type: Side Feed Type Mixer Seal
 Replacement: American SHARPE Mixer and Kettle Mechanical Seal
 Temperature: $\leq 120^{\circ}\text{C}$
 Pressure: $\leq 1.6\text{Mpa}$
 Speed: $\leq 1000\text{r/min}$
 Material: Q1, Q2, A, B, U1, U2, P, E, V, T, F, G, T2, M5

*Product description

SHARPE MIXER special mechanical seal for sharp agitator. The installation size fits perfectly with the original mechanical seal of the mixer. Assemble type single - end face structure, easy to install and replace. The sealing ring of non-pressure sintering silicon carbide, the matrix parts of corrosion resistant alloy steel and the auxiliary rubber sealing ring for high temperature and corrosion resistance, so that mechanical seal can adapt to various complicated working conditions.

*Apply to the host

SHARPE .

*Product features

Single end face set, static balance type.

Multiple springs, free rotation.

Horizontal installation, clamping type transmission.

SiC, 304/316L, fluoro rubber/silicone rubber.

Outside circulation flushing



* Replacement models

25SV25M-5.34 30SV25M-5.34 30SV25M-5.67
 40SV30M-5.45 50SV30M-5.45 50SV35M-4.34
 75SV35M-5.17

* The common specifications:

SCB428-2.5", SCB428-3", SCB428-3.5"

