

HMSR-01



Type: Slurry Pump Seal
Temperature: $\leq 150^{\circ}\text{C}$
Pressure: $\leq 0.8\text{Mpa}$
Speed: $\leq 1600\text{r/min}$
Material: Q1, Q2, U2, T, V, M1, F, G, M

*Product description:

Single end face packing series mechanical seals have short axial size, compact structure, convenient installation, simple use and high safety factor. They adopt single end face packing structure, durable and stable.

*Apply to the host:

ZiGong industrial pump manufacturers.

*Product features:

Zigong industrial pump HQSR-05 double end mounted mechanical seal series features short axial size, compact structure, convenient installation, simple use and high safety factor. It adopts single end mounted structure, durable and good stability, and is mainly applicable to gypsum slurry pump, limestone slurry pump, gypsum discharge pump, slag slurry pump, etc.

*Product parameters:

Temperature: $\leq 120^{\circ}\text{C}$
Pressure: $\leq 1.6\text{mpa}$
Solid particle content: $\leq 30\%$
Diameter: 32mm to 115mm
Suitable medium: water, oil, acid, alkali and other corrosive medium

*Scope of application:

Flue gas desulfurization, smelting, fine chemical industry, papermaking and other industries
Metallurgy Food and beverage industry, Water conservancy.