

## HMSR-02



Type: Slurry Pump Seal  
Temperature: -20 to +150°C  
Pressure:  $\leq 0.2\text{Mpa}$   
Speed:  $\leq 1800\text{r/min}$   
Material: Q1,Q2,U2,T,V,M1,F,G,M

### \*Product description:

ZGJ single cartridge seal series features short axial size, compact structure, easy installation, simple use, high safety factor, durability and good stability. It is mainly used for desulfurization of flue gas from coal-fired power plants, and is suitable for gypsum slurry pump, limestone slurry pump, gypsum discharge pump, and mine slag slurry pump, etc.

### \*Apply to the host:

ShiJiaZhuang strong pump manufacturers.

### \*Product features:

ZGJ single cartridge seal series features short axial size, compact structure, convenient installation, simple use and high safety factor. It adopts single end mounted structure, durable and good stability, and is mainly applicable to gypsum slurry pump, limestone slurry pump, gypsum discharge pump, slag slurry pump, etc.

### \*Product parameters:

Temperature:  $\leq 150\text{ }^{\circ}\text{C}$   
Pressure:  $\leq 1.6\text{ mpa}$   
Solid particle content:  $\leq 30\%$   
Diameter: 45mm to 170mm  
Suitable medium: water, oil, acid, alkali and other corrosive medium

### \*Scope of application:

Flue gas desulfurization, smelting, fine chemical industry, papermaking and other industries