


## HMSR-05



Type: Slurry Pump Seal  
Temperature:  $\leq 150^{\circ}\text{C}$   
Pressure:  $\leq 0.8\text{Mpa}$   
Speed:  $\leq 1400\text{r/min}$   
Material: Q1,Q2,U2,T,V,M1,F,G,M

### \*Product description:

ZiGong industrial pump ZBG double cartridge mechanical seals, using moving ring, static ring, spring, auxiliary seal ring shaft sleeve, seal seat and other main parts together, so in the installation is more convenient, fast, reliable seal, simple to use, good balance, arbitrary rotation.

### \*Apply to the host:

ZiGong industrial pump manufacturers.

### \*Product features:

Zigong industrial pump ZBG double cartridge mechanical seal series features short axial size, compact structure, convenient installation, simple use and high safety factor. It adopts single end mounted structure, durable and good stability, and is mainly applicable to gypsum slurry pump, limestone slurry pump, gypsum discharge pump, slag slurry pump, etc.

### \*Product parameters:

Temperature:  $\leq 120^{\circ}\text{C}$   
Pressure:  $\leq 1.6\text{mpa}$   
Solid particle content:  $\leq 30\%$   
Diameter: 32mm to 115mm  
Suitable medium: water, oil, acid, alkali and other corrosive medium

### \*Scope of application:

Flue gas desulfurization, smelting, fine chemical industry, papermaking and other industries  
Metallurgy Food and beverage industry, Water conservancy.

