

HMSR-08

Type: Slurry Pumps
Temperature: $\leq 150^{\circ}\text{C}$
Pressure: $\leq 1.4\text{Mpa}$
Speed: $\leq 20\text{m/s}$
Material: Q1,Q2,U2,T,V,M1,F,G,M



*Product description:

ZJ series low-pressure self-circulation double cartridge mechanical seals, using moving ring, static ring, spring, auxiliary sealing ring, shaft sleeve, seal seat and other main parts together into an assembly, so it is more convenient to install on the body, fast, reliable sealing, simple to use, good balance, arbitrary rotation.

*Apply to the host:

ShiJiaZhuang Industrial pump manufacturers.

*Product features:

ZJ series low-pressure self-circulation double cartridge mechanical seal series features short axial size, compact structure, convenient installation, simple use and high safety factor. It adopts single end mounted structure, durable and good stability, and is mainly applicable to gypsum slurry pump, limestone slurry pump, gypsum discharge pump, slag slurry pump, etc.

*Product parameters:

Temperature: $\leq 120^{\circ}\text{C}$
Pressure: $\leq 1.6\text{mpa}$
Solid particle content: $\leq 30\%$
Diameter: 50mm to 200mm
Suitable medium: water, oil, acid, alkali and other corrosive medium

*Scope of application:

Chemical, petroleum, paper, pharmaceutical, smelting, light industry, mining, thermal power and other industries .

