


HMSR-07

Type: Slurry Pump Seal
Temperature: $\leq 150^{\circ}\text{C}$
Pressure: $\leq 0.8\text{Mpa}$
Speed: $\leq 1000\text{r/min}$
Material: Q1,Q2,U2,T,V,M1,F,G,M



*Product description:

TianMen ZBD single cartridge mechanical seal series has short axial size, compact structure, convenient installation, simple use, high safety factor, adopts single end face packing structure, durable, good stability is mainly used for ZBG, ZBD pump series.

*Apply to the host:

TianMen pump manufacturers.

*Product features:

TianMen ZBD single cartridge mechanical seal series features short axial size, compact structure, convenient installation, simple use and high safety factor. It adopts single end mounted structure, durable and good stability, and is mainly applicable to gypsum slurry pump, limestone slurry pump, gypsum discharge pump, slag slurry pump, etc.

*Product parameters:

Temperature: $\leq 120^{\circ}\text{C}$
Pressure: $\leq 1.6\text{mpa}$
Solid particle content: $\leq 30\%$
Diameter: 50mm to 200mm
Suitable medium: water, oil, acid, alkali and other corrosive medium

*Scope of application:

Chemical, petroleum, paper, pharmaceutical, smelting, light industry, mining, thermal power and other industries .

