

## HMSR-09

Type: Slurry Pump Seal  
Temperature:  $\leq 150^{\circ}\text{C}$   
Pressure:  $\leq 0.8\text{Mpa}$   
Speed:  $\leq 1800\text{r/min}$   
Material: Q1, Q2, U2, T, V, M1, F, G, M



### \*Product description:

ZiBo HuaCheng ZJA series double cartridge mechanical seals, using moving ring, static ring, spring, auxiliary sealing ring, shaft sleeve, seal seat and other main parts combined into an assembly, so it is more convenient to install on the body, fast, reliable sealing, simple to use, good balance, arbitrary rotation.

### \*Apply to the host:

ZiBo HuaCheng pump manufacturers.

### \*Product features:

ZiBo HuaCheng ZJA series double cartridge mechanical seal series features short axial size, compact structure, convenient installation, simple use and high safety factor. It adopts single end mounted structure, durable and good stability, and is mainly applicable to gypsum slurry pump, limestone slurry pump, gypsum discharge pump, slag slurry pump, etc.

### \*Product parameters:

Temperature:  $\leq 120^{\circ}\text{C}$   
Pressure:  $\leq 1.6\text{mpa}$   
Solid particle content:  $\leq 30\%$   
Diameter: 25mm to 150mm  
Suitable medium: water, oil, acid, alkali and other corrosive medium

### \*Scope of application:

Chemical, petroleum, paper, pharmaceutical, smelting, light industry, mining, thermal power and other industries .

